



KS-25

Milling & Drilling Machine



KS-40

Milling & Drilling Machine





SPECIFICATIONS:

TYPE		KS- 25	KS- 30	KS- 40
Dia. of quill(mm)		∅ 85	∅ 96	∅ 96
Taper of spindle		MT3, R8	MT3, R8, NT130	MT3, R8, NT30
X & Y Travels		500 x 190	500 x 175	500 x 270
Spindle stroke(mm)		110	130	130
Spindle to disc(mm)		215	202	267
Spindle nose to table top		480	480	470
Head swivel around column		360°	360°	360°
Drilling capability(mm)		32	32	32
Tapping capability		19	19	19
Milling capability		76	76	76
Dia. of disc(mm)		95	115	115
Table size (Lx W)		660 x 190	730 x 210	730 x 210
Base size(LxW)		545 x 335	620 x 400	675 x 400
Spind Speeds & steps	50Hz	90-2150	100-2080	50-1250
	60Hz	110-2580	120-2500	60-1500
Motor		1HP	2HP	1HP
Machine size(LxWxH)		950x 1030 x 1080	1080x 1100x 1100	870x 1100x 1100
Machine weight(kg)		195kg	270kg	290kg
Size of cabinet stand		760 x 558 x 787	760 x 558 x 787	760 x 558 x 787