

Quick Set

DEPOSPEED-1008

Gantry Type Milling and Machining Center



MACHINE SPECIFICATIONS:

| | | |
|--|---|---------------------------------|
| TRAVEL | X axis | 1000mm |
| | Y axis | 800mm |
| | Z axis | 700 mm |
| | Spindle nose to table surface (Min / Max) | 100~800mm |
| TABLE | Size | 1, 350x 1, 300mm |
| | T-slot (W x NO. x P) | 18 x 11x 125mm |
| | Table Type | Fixed |
| SPINDLE (built-in) | Spindle speed | 200-14, 000 rpm |
| | Motor | 25kw |
| | Tool interface | HSK-A 80 |
| | Water chiller temp.control | ± 1° C of ambient temperature |
| FEED RATES | Cutting feed | 1-24, 000 mm / min |
| | XY Zrapid traverse | 1-24, 000 mm / min |
| AUTOMATIC TOOL CHANGER (Disk magazine) | Max. tool dia. | Ø 66mm |
| | Max. tool lengh | 300mm |
| | Max. tool weight | 12kg |
| | Tool storage capacity | 10Tools |
| COOLANT | Coolant pump | 0.58 kw |
| | Coolant tank capacity | 150L |
| AIR SUPPLY | Pressure / Consumption | 6kg /cm ² 500L / min |
| POWER SUPPLY | Capacity | 71 KVA |
| MACHINE SIZE | Machine dimension (L x W x H) | 3, 813x 3, 954 x 3, 450mm |
| | Machine weight | 15, 700 kg |