



KV.A- 50A

Table Automatic Feed Assembly

Vertical Metal Cutting Band Saws



KV.A- 100A

Table Automatic Feed Assembly

Vertical Metal Cutting Band Saws





KV-A SPECIFICATIONS:

Models		Unit	KV - 40A	KV - 50A	KV - 60A	KV - 100A
Cutting capacity	throat depth	mm(in)	410(16.13)	520(20.5)	600(23.63)	1000(39.38)
	max, work height	mm(in)	300(11.81)	310(12.38)	300(11.81)	300 (11.81)
Table size		mm(in)	660x 700(126 x 27.5)	600 x 700(26 x 27.5)	660 x 700(26 x 27.5)	660 x 700(26 x 27.5) 450 x 500(17.75 x 19.5)
Table inclination (4 ways)			L5° R15°	L5° R15°	L5° R15°	L5° R15°
Table stroke		mm(in)	350(13.78)	350(13.78)	350(13.78)	350(13.78)
Saw blade length		mm(in)	3350(132)	3880(153)	3970(156.31)	4540(178.63)
Saw blade width		mm	3-20	3-20	3-20	3-20
Saw blade speeds		m/min(fpm)	Low 20-85m/min (65-280fpm) High 120-500m/min (400-1640fpm)			
Butt welder capacity		mm(in)	4.2KVA, 3-20mm(0.13081)			
Drive motor		HP(KW)	2HP(1.5)	2HP(1.5)	2HP(1.5)	2HP(1.5)
Net Weight (approx.)		kgs(lbs)	590(1298)	650(1430)	850(1870)	950(2090)
Gross weight (approx.)		kgs(lbs)	710(1562)	770(1694)	970(2134)	1070(2354)
Measurement (LxWxH)		mm(in)	1350 x 1100 x 2100 (53.19 x 43.31 x 82.81)	1450x 1100x 2140 (57 x 43.31 x 84.31)	1570x 1100x 2140 (62 x 43.31 x 84.31)	1920 x 1100 x 2140 (75.63 x 43.31 x 84.31)